

**KINCROME**   
PROFESSIONAL QUALITY TOOLS

# TOW BEHIND SPRAYER 50L BROADCAST/SPOT

**50  
LITRE  
TANK**

**3.8LPM  
MAX  
FLOW  
RATE**

**100%  
DUTY  
CYCLE**

**SUITABLE FOR  
WATER,  
HERBICIDES  
& PESTICIDES  
INC. ROUNDUP®**



**K16003**

**ED1 APRIL 2017**



# K16003

**50L Tow Behind Sprayer**  
(ADD YOUR SPRAYERS BATCH CODE HERE)  
BATCH CODE: \_\_\_\_\_

## Owner's Manual

**M797490A.1**

Instructions for Assembly, Testing, Operation, Servicing, and Storage

**Tow Behind Sprayers:** For outdoor use with non-potable liquids such as agricultural pesticides and other water-based liquids.

### **WARNING**

**READ and UNDERSTAND the Owner's Manual completely before using this sprayer.** Assemble, test, and use only in accordance with the Owner's Manual instructions.

**READ and FOLLOW chemical label instructions.** Pesticides are hazardous chemicals.

**KNOW emergency procedures BEFORE handling chemicals.** Sprayer leaks, bodily chemical contact, poisoning, and spills require immediate response.

**AVOID inhaling, ingesting, or coming into contact with any chemicals.**

**WEAR personal protective gear when filling, using, cleaning, and servicing the sprayer.**

**KEEP sprayer and spray materials away from children and pets.** Pesticides are especially toxic to them.

**EXERCISE CAUTION in vehicle handling when towing/hauling a filled sprayer to avoid loss of control or sprayer overturning.**

**DO NOT TURN ON POWER to sprayer until ready to spray** in order to avoid unintentional spray release.

**ALWAYS** keep a fire extinguisher rated "AB(E)" (Dry Chemical) nearby.

**Improper use of the sprayer or handling of chemicals could result in serious injury or illness to the operator or nearby persons/animals, or could cause damage to the environment.**

**Only use the cable clamps provided with the sprayer to connect it with the vehicle battery**

**\*\* This sprayer is recommended for use in spraying non-flammable liquids such as pesticides, water for plants/trees or dust control, ice control chemicals that do not contain calcium chloride, sodium chloride, magnesium chloride, or other forms of chlorine, or water-based non-flammable sealants or stains for outdoor wood surfaces. The pump should not be used to transfer any product intended for human consumption. WE RECOMMEND THAT THE SPRAYER NOT BE USED FOR OTHER PURPOSES ONCE IT HAS BEEN USED FOR SPRAYING PESTICIDES. Any chemical will leave some residual in the tank liner or sprayer components, even after the sprayer has been properly cleaned. These residual chemicals can have unexpected effects on future uses. For example, spraying water or other liquids that are contaminated with residual pesticide may result in unforeseen hazards to plant or animal life. This sprayer should not be used by people with physical, sensory or mental capabilities or lack of experience and knowledge.**

**Any Questions, Comments, Problems, or Parts Enquiries**

***Call Kincrome Customer Service 1300 657 528***



## Hazard Signal Word Definitions






	<p>This is the safety alert symbol. It is used to alert you to potential personal injury hazards. Obey all safety messages that follow this symbol to avoid possible injury or death.</p>
	<p>DANGER (red) indicates an imminently hazardous situation which, if not avoided, will result in death or serious injury.</p>
	<p>WARNING (orange) indicates a potentially hazardous situation which, if not avoided, could result in death or serious injury.</p>
	<p>CAUTION (yellow) indicates a potentially hazardous situation which, if not avoided, may result in minor or moderate injury.</p>
	<p>CAUTION (yellow) used without the safety alert symbol indicates a potentially hazardous situation which, if not avoided, may result in property damage.</p>

fig01453

## Tools Required for Assembly

- 1/2" Spanner
- Torque Wrench with minimum 5 ft-lb
- Combination Pliers
- Phillips Head Screwdriver
- Flat Head Screw Driver

## Table of Contents

Intended Use .....	5
Summary of Important Safety Information.....	6
Warning Label Location .....	9
Unpacking .....	10
Unpacking the Manual Bag .....	11
Assembly.....	12
Machine Components .....	30
Operation – Important Safety Information .....	31
Operation – Preparing the Sprayer for Each Use.....	36
Operation – Using the Sprayer.....	37
Storage .....	46
Troubleshooting .....	47
Specifications.....	49
Exploded View – K16003 50 Litres Tow Behind Sprayer .....	50
Appendix A –Broadcast Spray Calibration Tables .....	52
Limited Warranty.....	53

## Intended Use

The sprayer is intended for use in spraying agricultural pesticides and other non-flammable liquids.

### **SPRAYING PESTICIDES:**

Pesticides are hazardous chemicals that must be handled with caution as directed throughout this manual and on the pesticide label. Pesticides are regulated by your local states Environmental Protection Agency (EPA) and defined as:

*A substance or mixture of substances intended for preventing, destroying, repelling or mitigating any pest, typically acting as a herbicide, fungicide or insecticide*

The sprayer is intended for use in spraying pesticides in liquid form only. The sprayer is NOT intended for use in spraying pesticides in dry or aerosolized form, or for use with fumigants.

This sprayer comes equipped with a spot spray gun and a broadcast nozzle. Use the spot spray gun if you desire to apply pesticide only on selected plants. Use the broadcast boom if you wish to spray large ground areas.

### **SPRAYING OTHER LIQUIDS:**

In addition to spraying pesticides, this sprayer may be used to spray other **non-flammable** liquids. Example uses include: watering plants/trees or spraying water for dust control, applying ice control chemicals that do not contain calcium chloride, sodium chloride, magnesium chloride, or other forms of chlorine, or applying water-based, non-flammable sealant or stain to outdoor wood surfaces. Pump will be damaged and warranty voided if applying sodium chlorine or other chlorine or bleach related chemicals.

However, **WE RECOMMEND THAT THE SPRAYER NOT BE USED FOR OTHER PURPOSES ONCE IT HAS ALREADY BEEN USED FOR SPRAYING PESTICIDES.** Any chemical will leave some residual in the tank liner or sprayer components, even after the sprayer has been properly cleaned. These residual chemicals can have unexpected effects on future uses. For example, spraying water or other liquids that are contaminated with residual pesticide may result in unforeseen hazards to plant or animal life.

**Contact Kincrome Customer Service on 1300 657 528 for any questions about the appropriate use of the sprayer and/or optional accessories.**

## Summary of Important Safety Information

### WARNING

Read and understand **this owner's manual** completely before using the sprayer. Read each **chemical label's instructions** before handling the chemical.

*Improper use of the sprayer or handling of chemicals could result in serious injury or illness for the operator or nearby persons/animals, or cause damage to the environment.*

LISTED BELOW is a summary of safety information of particular importance. See individual sections of this owner's manual for more details.

#### ----- DURING ASSEMBLY -----

- **EXERCISE CAUTION** when attaching remote switch to battery terminals. Follow the steps listed in the Assembly section of this manual in *exact sequence* when connecting the sprayer's remote switch battery clamps to the battery terminals. *Caution must be exercised to avoid contact with battery acid and to prevent sparking.*
- **CHECK and TEST completed assembly** as directed in this manual. Serious injury could result from chemical leaks if sprayer is improperly assembled.
- **DO NOT MODIFY** sprayer design.

#### ----- DURING OPERATION -----

##### General Chemical Safety

- **READ and FOLLOW** each chemical label's instructions and warnings.
- **AVOID** inhaling, ingesting, or coming into contact with any chemicals.
- **KNOW** applicable licensing and regulatory requirements for the chemical you plan to use.
- **KNOW** emergency procedures before handling chemicals. Carefully review "Chemical Accident Procedures" listed below and later in this manual. Also see First Aid instructions on the chemical label.
- **WEAR** protective clothing, eye protection, and chemical resistant gloves when filling, using and cleaning the sprayer. Wear additional protective gear, such as facemask or apron, as recommended on the chemical label.
- **EXERCISE EXTRA CAUTION** around children and pets. Pesticides are especially toxic to them. Keep sprayer and spray materials away from them at all times.
- **DO NOT MIX OR POUR** chemicals in an enclosed, unventilated area
- **DO NOT USE** flammable or corrosive chemicals in the sprayer.
- **FLUSH** the sprayer before switching chemicals in order to prevent dangerous chemical interactions.
- **STORE** pesticides in a correctly labeled container and in a secure location.
- **MONITOR** the health of operators frequently exposed to pesticides, as recommended by the chemical label or local/federal regulations.

##### Chemical Application Safety

###### Before Spraying

- **INSPECT and PREPARE** sprayer before each use as directed in this manual.
- **DO NOT TURN ON POWER** to sprayer until ready to spray in order to avoid unintentional spray release.
- **MAKE SURE BROADCAST NOZZLE IS ORIENTED** to spray straight back before starting the sprayer. An incorrectly positioned broadcast nozzle may spray chemicals on you or others.
- **DO NOT SPRAY** when wind speed exceeds 6.5 km/h in order to minimize spray drift.
- **CLEAR** work area of people/ pets and **POST** warning notices to restrict access for the period recommended on chemical label.
- **KEEP** sprayer and spray away from children/pets. Pesticides can be especially toxic to children and animals.
- **DO NOT ALLOW** anyone younger than 16 to operate sprayer since pesticides are especially toxic to children.

###### During Spraying

- **DO NOT OVERAPPLY** pesticide. Apply at rate recommended by chemical manufacturer. Excess pesticide can be dangerous to humans/animals, damage desirable plants, and contaminate soil and water sources.

## Summary of Important Safety Information (cont'd)

- **DO NOT EAT, DRINK, SMOKE, RUB YOUR EYES, or TOUCH YOUR BARE SKIN** while handling chemicals and spraying.
- **NEVER POINT THE SPRAY GUN** at people or animals.
- **EXERCISE EXTRA CAUTION** when spraying near areas accessible to children and pets.
- **CLEAN up spills immediately** per instructions on the chemical label.
- **TURN OFF vehicle and set brake or block wheels, TURN OFF power to sprayer, and RELIEVE system pressure** before leaving sprayer unattended.
  - **SEE troubleshooting section of this manual before attempting any repairs.** Wear personal protective equipment and follow safety instructions.

### After Spraying

- **CLEAN sprayer immediately after use** according to the directions provided in this manual.
- **DECONTAMINATE yourself after you are done spraying** and have cleaned the sprayer. Wash all exposed areas of the body with soap and water, and remove and launder clothing.
- **DISPOSE OF or STORE remaining chemicals in secure storage with correctly marked container.**

### Towing/Hauling Safety

- **READ towing/hauling safety instructions** in your towing/hauling vehicle manual.
- **DO NOT ALLOW drivers younger than 16** to operate the towing/hauling vehicle with the filled sprayer attached.
- Check your local state regulations for further information regarding ATV use and laws.
- **MAKE SURE SPRAYER IS SECURELY ATTACHED to vehicle.**
- **EXERCISE CAUTION in vehicle handling when towing/hauling filled sprayer** to avoid loss of control or overturning.
- **Keep speed to a minimum** so you can maintain control. Reduce speed prior to turns.
- **Allow for wider turns** and for **more distance to stop.**
- **Avoid any sudden** steering maneuvers, starts, or stops that could create sway.
- **SLOW DOWN and EXERCISE EXTRA CAUTION** on sloped or uneven terrain. **Pick the most level route possible. Drive up and down slopes when necessary, rather than across. Use a vehicle equipped with a roll over protection system (ROPS) if you will be working on non-level terrain.**
- **BE AWARE** of the added length of the sprayer and that visibility may be reduced **when making turns or backing up.**
- **DO NOT RIDE or TRANSPORT cargo** on the sprayer.
- **COMPLY WITH** all local, state, and federal towing requirements if you will be towing on public roads.
- **TURN OFF** both sprayer and vehicle, and **SET BRAKES or BLOCK WHEELS before leaving unattended.**

### Chemical accident procedures

Immediate response is necessary in the event of sprayer leaks, bodily chemical contact, poisoning, or spills.

Sprayer leak	
	<b>If the sprayer develops a leak, immediately stop spraying.</b> Turn off power to the sprayer and follow directions below, as applicable.

## Summary of Important Safety Information (cont'd)

<b>Bodily chemical contact</b>	<p><b>Personal contamination can occur when chemicals splash, spill, or spray directly onto a person.</b></p> <ol style="list-style-type: none"> <li>1. Immediately follow First Aid instructions on <u>chemical label</u>.  <u>General procedures can include:</u> <ol style="list-style-type: none"> <li>a) Eyes – immediately flush with water.</li> <li>b) Skin – wash all contaminated skin surfaces with soap and water.</li> <li>c) Clothing – remove contaminated clothing. Dispose of heavily contaminated clothing per chemical label instructions.</li> </ol> </li> <li>2. Seek medical advice if instructed on the label or the victim experiences symptoms of harmful effects. Bring the chemical label for reference.</li> </ol>
<b>Poisoning by ingestion or inhalation</b>	<p><b>In case of poisoning from ingestion or inhalation:</b>  <i>If the victim has collapsed or is not breathing, <u>call 000</u>.</i> Otherwise:</p> <ol style="list-style-type: none"> <li>1. If you are the victim, immediately seek assistance from nearby personnel because you may become incapacitated.</li> <li>2. Immediately follow first aid instructions on <u>chemical label</u>.</li> <li>3. Call a poison control center for further advice. <b>In Australia. Call 13 11 26.</b>              Have the chemical label available for reference.</li> </ol>
<b>Chemical spills</b>	<p><b>Chemical spills must be quickly contained and properly cleaned up.</b>              Refer to the chemical label for any specific clean-up instructions.  <u>General procedures include:</u></p> <ol style="list-style-type: none"> <li>1. <b>Controlling</b> the spill by stopping the source of the spill.</li> <li>2. <b>Containing</b> the spill so that it does not spread and get into water sources.</li> <li>3. <b>Cleaning up</b> the spill immediately.</li> <li>4. <b>Seeking additional advice</b> from:             <ul style="list-style-type: none"> <li>- <u>Chemical manufacturer</u>. See chemical label for contact information.</li> <li>- Contact the <u>APVMA (Australian Pesticides &amp; Veterinary Medicines Authority)</u>, by emailing <a href="mailto:enquiries@apvma.gov.au">enquiries@apvma.gov.au</a> or calling (02) 6210 4701.</li> </ul> </li> </ol>



## Warning Label Location

### WARNING

**READ and UNDERSTAND the Owner's Manual completely before using this sprayer.**

Assemble, test, and use only in accordance with the Owner's Manual instructions.

**READ and FOLLOW chemical label instructions.** Pesticides are hazardous chemicals which must be handled carefully.


**KNOW emergency procedures BEFORE handling chemicals.** Sprayer leaks, bodily chemical contact, poisoning, and spills require immediate response.

**AVOID inhaling, ingesting, or coming into contact with any chemicals.**

**EXERCISE CAUTION in vehicle handling.** Vehicle will be less stable and handle very differently with filled sprayer attached.

**DO NOT TURN ON POWER to sprayer until ready to spray** in order to avoid unintentional spray release.

**Improper use of the sprayer or handling of chemicals could result in serious injury or illness to the operator or nearby persons/animals, or could cause damage to the environment.**



### WARNING

DO NOT PUMP FLAMMABLE FLUIDS. DO NOT USE PUMP IN AN EXPLOSIVE ENVIRONMENT. READ AND UNDERSTAND THE OWNER'S MANUAL COMPLETELY BEFORE USING. RELIEVE SYSTEM PRESSURE BEFORE PERFORMING MAINTENANCE.

Part#	Description
K16004-60	Chemical Label
K16003-37	Pump Label

**Always make sure safety labels are in place and in good condition.** If a safety label is missing or not legible, order new labels or unsafe operation could result.


**To order replacement safety labels, call Kincome Customer Service on 1300 657 528.**

# Unpacking


## Closely inspect all contents in the shipping carton.

Note that some parts are shipped inside the tank.


- If you have missing or damaged components, please contact Kinchrome Customer Service on 1300 657 528.




**K16003-25**  
Tank  
Qty 1




**K16003-16**  
Spot Spray Gun  
Assembly  
Qty 1




**K16003-33**  
Gun Hose  
Qty 1




**Manual Bag**  
Qty 1




**K16003-6 & 19, K16000-12**  
Upper Hose Storage Hook  
Qty 1




**K16003-18, 31**  
Lower Hose Storage  
Hook  
Qty 1




**K16003-23**  
Hitch Bracket  
Qty 2




**K16003-1, 3, 9, 10, 26, 29, 32,  
K16000-2**  
Rear Broadcast Assembly  
Qty 1




**K16003-17**  
Rear Tank  
Mounting Bracket  
Qty 2




**K16003-21**  
Axle  
Qty 1




**K16003-20, 22**  
Tow Bar Assembly  
Qty 1




**K16003-28**  
Pump Mounting  
Bracket  
Qty 1



**K16003-32**  
Draw Tube  
Qty 1



**K16003-14**  
Wheels/Tyres  
Qty 2




**K16003-15**  
Pump  
Qty 1




**K16003-43, 44, 45, 46,  
K16001-15**  
Regulator Assembly  
Qty 1

## Unpacking the Manual Bag


The following items are found in the manual bag.




K16000-2  
Hose Clamp  
Qty 5




K16001-13  
Hose Clip  
Qty 1




K16003-30  
Suction Hose  
Qty 1




K16003-41  
#10-24 x 15mm  
Screw  
Qty 3




K16001-3  
#10-24 x 25mm  
Screw  
Qty 1




K16003-6  
#10-24 x 10mm  
Screw  
Qty 4




K16003-39  
Hook and Loop Tape  
Qty 1




K16000-5  
Wire Harness w/  
Remote Switch  
Qty 1




K16000-9  
Strainer/Filter  
Qty 1




K16003-27  
Axle Pin  
Qty 2




K16003-44  
3/8" QC HB Elbow  
Qty 1




5/16" x 2" Bolt  
Qty 4




5/16" x 1/2" Bolt  
Qty 11




5/16" Nut  
Qty 4



K16003-7  
Axle Washer  
Qty 4



K16003-5  
Drain Cap  
Qty 1



K16003-2  
Rubber Washer  
Qty 1

## Assembly


### Step 1 – Tow Bar Hitch Assembly

- Insert bolts through hitch bracket holes. Secure with nuts until hand tight.
- Ensure hitch pin holes are aligned and tighten bolts to 20 Ft.-Lbs.


### Tools Needed

- 1/2" wrench
- Torque wrench


### Fasteners Needed from Owner's Manual Bag:



5/16" x 2" Bolt  
Qty 2



5/16" Nut  
Qty 2



## Assembly (cont'd)


### Step 2 – Cart Assembly

- Insert bolts through rear bracket holes and tow bar.
- Ensure rear brackets top surface is flush with tow bar top surface.
- Secure with nuts until hand tight.


### Tools Needed

- N/A


### Fasteners Needed from Owner's Manual Bag:



5/16" x 2" Bolt  
Qty 2



5/16" Nut  
Qty 2




## Assembly (cont'd)

### Step 3 – Axle Assembly

- Insert axle through rear brackets and tow bar.
- Torque rear bracket bolts from Step 2 to 20 Ft.-Lbs.

### Tools Needed

- 1/2" wrench
- Torque wrench



## Assembly (cont'd)





### Step 4 – Tank to Cart Assembly

- Set tank on ground upside down. Align cart assembly with bottom of tank and secure with bolts.
- Torque bolts to 5 Ft.-Lbs.
- Note: if tank inserts do not align with cart, loosen cart bolts then insert bolts into tank inserts. Torque cart bolts to 20 Ft.-Lbs.
- Press rubber washer into drain cap with finger.
- Thread drain cap on to tank until hand tight.


### Tools Needed

- 1/2" wrench
- Torque wrench


### Components Needed from Owner's Manual Bag:




5/16" x 1/2" Bolt  
Qty 4  
82014



K16003-5  
Drain Cap  
Qty 1



K16003-2  
Rubber Washer  
Qty 1



## Assembly (cont'd)


### Step 5 – Wheel Assembly

- Install wheels onto axle.
- Slide washers onto axle.
- Insert axle pins into holes in axle.
- Note: check that tires are inflated to 30 PSI.




### Tools Needed

- Pliers
- PSI Gauge


### Fasteners Needed from Owner's Manual Bag:



K16003-27  
Axle Pin  
Qty 2



K16003-7  
Axle Washer  
Qty 4





## Assembly (cont'd)


### Step 6 – Draw Tube Assembly

- Remove cap from sprayer tank.
- Insert draw tube through grommet. Note: wet draw tube with soapy water to ease installation.
- Place strainer on end of draw tube.
- Push draw tube into grommet until strainer reaches the bottom of the tank.

### Tools Needed

- N/A


### Components Needed from Owner's Manual Bag:



K16000-9  
Strainer/Filter  
Qty 1



K16003-30  
Suction Hose  
Qty 1



## Assembly (cont'd)


### Step 7 – Hose Wrap Assembly

- Install upper and lower hose wrap brackets.
- Secure with bolts and torque to 5 Ft.-Lbs.


### Tools Needed

- 1/2" wrench
- Torque wrench

### Fasteners Needed from Owner's Manual Bag:



5/16" x 1/2" Bolt  
Qty 4



## Assembly (cont'd)


### Step 8 – Pump Riser

- Place pump riser on top of tank and align the holes with the 4 threaded tank inserts.
- Tighten screws until pump riser is secure.


### Tools Needed

- Phillips head screwdriver

### Fasteners Needed from Owner's Manual Bag:



K16003-6  
#10-24 x 10mm Screw  
Qty 4




## Assembly (cont'd)

### Step 9 – Regulator Assembly

- Install QC x 1/2" straight hose barb into bypass of regulator. Secure with steel clip.
- Thread pressure gauge into 1/4" NPT port on front side of regulator (the side of the regulator with the "BYPASS" label.)
- Thread 1/4" MPT x 3/8" straight hose barb into the 1/4" NPT port on back side of regulator.
- Install QC x 3/8" hose barb elbow into outlet of regulator. Secure with steel clip.

### Tools Needed

- N/A



## Assembly (cont'd)


### Step 10 – Pump Assembly

- REMOVE Red Travel Plugs from Inlet & Outlet Port before assembly.
- Install inlet port of the regulator into outlet port of the pump. Secure with steel clip.
- Install QC x 3/8" hose barb elbow into inlet of pump. Secure with steel clip.
- Apply soap to the bypass fitting on the bottom of the regulator and press bypass fitting into the tank grommet.
- Install (1) long screw through tether and into the front left pump foot and secure into pump rise holes.
- Install (3) short screws into the remaining pump feet and secure into pump riser holes. Note: damage could occur to rubber pump feet if screws are over-tightened.

### Tools Needed

- Phillips head screwdriver

### Fasteners Needed from Owner's Manual Bag:



## Assembly (cont'd)


### Step 11 – Boom Hose Assembly

- Align boom bracket assembly with threaded inserts on rear of tank. Secure with bolts and torque to 5 Ft.-Lbs.
- Slide hose clamp over hose.
- Slide hose over pump outlet hose barb. Tighten with hose clamp.



### Tools Needed

- 1/2" wrench
- Torque wrench
- Flat head screw driver


### Fasteners Needed from Owner's Manual Bag:



5/16" x 1/2" Bolt  
Qty 2



K16000-2  
Hose Clamp  
Qty 1



## Assembly (cont'd)


### Step 12 – Draw Tube Hose Assembly

- Slide hose clamps over ends of draw tube hose.
- Slide one end of draw tube hose onto pump inlet hose barb.
- Slide other end of draw tube hose onto draw tube PVC.
- Secure both ends with hose clamps and tighten.


### Tools Needed

- Flat head screw driver

### Fasteners Needed from Owner's Manual Bag:



K16000-2  
Hose Clamp  
Qty 2



## Assembly (cont'd)


### Step 13 – Attach gun hose to spot spray gun

- Install hose clamp on hose
  - Slide hose clamp over the end of the hose
  - Push the hose onto the hose barb
  - Slide the hose clamp over the hose barb
  - Tighten the hose clamp


### Tools Needed

- Flat head screwdriver
- Torque screwdriver

### Fastener Needed from Owner's Manual Bag:



K16000-2  
Hose Clamp  
Qty 1





## Assembly (cont'd)


### Step 14 – Gun Hose Assembly

- Route gun hose through hose clip and hose clamp.
- Slide gun hose over hose barb from boom hose assembly.
- Tighten hose clamp.
- Secure hose clip to tank with bolt and torque to 5 Ft.-Lbs.


### Tools Needed

- 1/2" wrench
- Torque wrench
- Flat head screwdriver


### Component Needed from Owner's Manual Bag:




K16000-2  
Hose Clamp  
Qty 1



5/16" x 1/2" Bolt  
Qty 1



K16001-13  
Hose Clip  
Qty 1




## Assembly (cont'd)

### Step 15 – Sprayer to Tow Vehicle Assembly

- Secure the sprayer to the tow vehicle with a hitch pin (not included)
- Make sure broadcast nozzle is pointed straight down. If it is not, loosen the nozzle retaining nut, orient the opening of the broadcast nozzle to point straight down, then retighten the nozzle retaining nut.

### Tools Needed

- N/A



## Assembly (cont'd)

### Step Sixteen: Connect remote switch to vehicle battery

#### **⚠ WARNING**

Batteries are hazardous because they contain caustic acid, can emit explosive gases, and can cause electric shock.

*Caution must be exercised when making connections to a battery to avoid shock and contact with the acid, and to prevent any sparking that could lead to an explosion.*

ALWAYS follow the safety instructions and steps listed below in *exact sequence* when connecting the sprayer's remote switch to the battery terminals.

#### **1. Preparatory safety**

##### **Preparatory safety steps:**

- ALWAYS use eye protection
- NEVER smoke or work near sparks or other sources of ignition.
- NEVER touch both battery terminals at the same time or with any non-insulated tools.
- If battery acid contacts skin or clothing, flush immediately with water and neutralize with baking soda.

#### **2. Connect remote switch to battery**

##### **Connect the sprayer's remote switch to the vehicle battery using the following procedure:**


- a) Disconnect the vehicle battery ground wire.
- b) Connect the remote switch's **red** battery clamp to the **positive(+)** terminal of the battery.
- c) Connect the remote switch's **black** battery clamp to the **negative(-)** terminal of the battery.
- d) Reconnect the vehicle battery ground wire.

**WARNING:** Always connect in this sequence to avoid possible shock.

#### **3. Connect remote switch to pump power cord**

##### **Connect the remote switch to the pump power cord:**

Note: Make sure the power switch is in the OFF position on the remote switch.



## Assembly (cont'd)

<b>4. Verify connection</b>	<b>Verify a complete connection has been made</b> by checking with a DC voltmeter, or by <i>briefly</i> turning the <u>remote switch</u> to the ON position and listening for pump activation.
<b>5. Attach remote switch to vehicle</b>	<b>Using supplied hook and loop pad, affix remote switch to vehicle in a position that is easily reached from the driver's seat.</b>
<b>6. Disconnect after use</b>	<p><b>AFTER EACH USE, disconnect power to the sprayer</b> by disconnecting the sprayer's <u>pump cord</u> from the <u>remote switch</u> – <i>the <u>remote switch</u> may remain connected to the battery.</i></p> <p><i>NOTE: It is important to disconnect power to the sprayer when not in use for safety reasons. ALWAYS verify that the power has been disconnected or the remote switch is in the OFF position before adding chemicals or servicing.</i></p>
<b>7. To disconnect permanently</b>	<p><b>When it is necessary to disconnect the sprayer's <u>remote switch</u> from the battery, use the following procedure:</b></p> <ol style="list-style-type: none"> <li>1. Disconnect <u>sprayer's pump cord</u> from the <u>remote switch</u>.</li> <li>2. Disconnect the <u>remote switch</u> from the vehicle battery as follows: <ol style="list-style-type: none"> <li>a) Disconnect vehicle battery ground wire.</li> <li>b) Disconnect the <u>remote switch's black</u> battery clamp from the <i>negative(-)</i> terminal of the vehicle battery.</li> <li>c) Disconnect the <u>remote switch's red</u> battery clamp from the <i>positive(+)</i> terminal of the vehicle battery.</li> <li>d) Reconnect the vehicle battery ground wire.</li> </ol> </li> </ol> <p><b>WARNING:</b> Always disconnect in this sequence to avoid possible shock.  <i>(Remember that on some vehicle models, you may need to remove the sprayer to access the battery)</i></p>

### Step Fifteen: Check and test completed assembly.

#### **WARNING**

##### Check and test completed assembly

Serious injury could result from chemical leaks if sprayer is improperly assembled or the design of the sprayer is modified.  
Follow the steps below to ensure the sprayer is properly assembled. Never modify the sprayer design.

<b>1. Check assembly</b>	<p><b>Check assembly to assure the sprayer is properly assembled and in safe working condition:</b></p> <ol style="list-style-type: none"> <li>a) Check that the gun clip screws are tight, hose clamps are secure, and tank straps are properly fastened.</li> <li>b) While it is unlikely that factory assembled components become loose, they should also be checked to make sure they are tight.</li> </ol>
--------------------------	---


## Assembly (cont'd)

### 2. Test with water

#### Test the system for leaks with water:

- a) Fill the tank with water.
- b) Connect the remote switch to the pump power cord and turn the remote switch ON. The pump is an "on demand" pump. When turned on, the pump will prime itself, and then turn off. When the gun trigger is squeezed, the pump will automatically start.
- c) Operate the spray gun by squeezing the gun trigger.
- d) Check for leaks throughout the system. If a leak is detected, fix the leak and re-test the system with water until no leaks are detected.

## Machine Components



1. **Hitch Bracket:** The hitch mount connects the vehicle hitch to the sprayer.
2. **Hose Wrap:** The built-in hose wrap provides a storage location for the gun hose on the tank.
3. **Gun Clip:** Use the gun clips to store the spray gun.(Also located on the side of the tank)
4. **Spot Spray Gun:** Use the spray gun to apply chemical to specific areas.
5. **Gun Hose:** The 11-foot gun hose transfers chemical from the pump to the spray gun.
6. **Fill Cap:** The fill cap has a vent to allow air to enter the tank as the chemical is dispensed.
7. **Remote Switch:** The remote switch connects the battery to the pump power cord and allows the operator to turn the sprayer pump on and off.
8. **Broadcast Valve:** The broadcast valve shuts off chemical to the rear broadcast nozzle.
9. **Suction Tube:** The suction tube is the inlet line for the pump. The suction tube has a suction strainer inside the tank to prevent debris from entering the pump.
10. **Sprayer Pump:** The sprayer pump makes the chemical flow to the spray gun and nozzles.
11. **Pump Power Cord:** Pump power cord and switch.
12. **Rear Broadcast Assembly:** The rear broadcast assembly houses the broadcast nozzle.
13. **Broadcast Nozzle:** The nozzle meters and distributes the chemical to a large area.
14. **Sprayer Tank:** The sprayer tank holds the chemical.
15. **Tyres:** The tyres have a wide tread to prevent turf damage.
16. **Tank Drain:** The tank drain is the location where fluid can be emptied from the tank.

## Operation – Important Safety Information

Now that you have completed and tested your assembly, there is some important safety and health information you need to know with regard to handling and spraying chemicals, as well as vehicle handling with the sprayer attached.

### WARNING

Carefully read and make sure you understand the following safety information before using the sprayer.

### General Chemical Safety:

### WARNING

Pesticides are hazardous chemicals.

Heed the warnings below and follow all instructions carefully.

Improper handling of chemicals can result in serious injury or illness, or cause damage to the environment.

- **Chemical label.** ALWAYS READ and FOLLOW all chemical label instructions.
- **Licensing/regulation.** Refer to any applicable licensing restrictions or state/federal regulations with regard to the application of the particular chemical you plan to use.
- **Emergency procedures.** Before handling chemicals, carefully review the "[Chemical Accident Procedures](#)" listed later in this section, as well as the "Statement of Practical Treatment" on the chemical label.
- **Inhalation/contact.** ALWAYS take precautions to avoid inhaling or coming into contact with the chemical.
- **Personal protective equipment.** ALWAYS wear protective clothing, eye protection, and chemical-resistant gloves when filling, using and cleaning the sprayer. Wear additional protective gear (such as facemask or apron) as recommended on the chemical label.
- **Children/pets.** Pesticides can be especially toxic to children and animals. ALWAYS exercise extra caution around children. Keep sprayer and all spray materials away from children and animals.
- **Ventilation.** ALWAYS ensure there is adequate ventilation when mixing, pouring, or spraying.
- **Flammables.** NEVER use any flammable chemicals in the sprayer.
- **Corrosives.** DO NOT use corrosive chemicals in the sprayer. They can weaken the sprayer and its parts, resulting in leaks. Check with the chemical manufacturer to ensure chemical is compatible with all components of the sprayer.
- **Chemical interaction.** ALWAYS flush the sprayer before switching chemicals. Different chemicals may interact dangerously with each other.
- **Chemical storage.** ALWAYS store pesticides in a properly labeled container and in a secure location per the manufacturer's recommendations.
- **Health monitoring.** Monitor the health of operators who are frequently exposed to pesticides, as recommended by the chemical label or local/federal regulations.

## Operation – Important Safety Information (cont'd)

### Chemical Application Safety:

#### **WARNING**

Caution must be used when spraying chemicals to avoid unsafe exposure to humans and the environment.

Heed the warnings below and follow all instructions carefully.

#### Before Spraying

- **Sprayer prep.** ALWAYS inspect and prepare the sprayer before use according to the directions provided in this manual.
- **Keep sprayer off.** Do not turn on power to the sprayer until ready to spray in order to avoid unintentional spray release.
- **Broadcast nozzle down.** Make sure broadcast nozzle is oriented to spray straight down before starting the sprayer. An incorrectly positioned broadcast nozzle may spray chemicals on you or others.
- **Wind speed.** NEVER spray when wind speed exceeds 6.5 km/h in order to minimize spray drift.
- **Clear area/post.** ALWAYS keep the work area clear of people and pets. POST warning notices to restrict access by the public for the period recommended on chemical label.
- **Operator age.** You must be 16 years of age or older to operate this sprayer. Pesticides are especially toxic to children.

#### During Spraying

- **Over application.** DO NOT over apply pesticide. Apply at a rate recommended by chemical manufacturer. Excess pesticide can be dangerous to humans, damage desirable plants, and contaminate soil and water sources.
- **Never point gun.** NEVER point the spray gun at people or animals.
- **Children/pets.** ALWAYS exercise extra caution when spraying near areas accessible to children and pets.
- **Eating/smoking.** DO NOT eat, drink, smoke, rub your eyes, or touch any part of your bare skin while handling chemicals and spraying.
- **Heat/flames.** DO NOT spray near open flames or sources of heat.
- **Spills.** ALWAYS clean up spills immediately per instructions on the chemical label.
- **Unattended.** ALWAYS turn off vehicle and set brake or block wheels, turn off power to sprayer, and relieve system pressure before leaving sprayer unattended.
- **Troubleshooting.** ALWAYS refer to the safety instructions in the Troubleshooting Section before attempting any repairs.

#### After Spraying

- **Clean sprayer.** ALWAYS clean the sprayer immediately after use according to the directions provided in this manual.
- **Decontaminate.** ALWAYS decontaminate yourself immediately after you are finished spraying and handling chemicals. Wash all exposed areas of the body with soap and water and remove and launder clothing.
- **Chemical disposal/storage.** ALWAYS dispose of or store remaining chemicals properly as recommended on the chemical label.



## Operation – Important Safety Information (cont'd)

### Towing/hauling Safety:

#### **WARNING**

The filled sprayer is very heavy. It can crush and cause serious injury if it rolls out of control or tips over.

Follow the instructions below for safely towing the sprayer.

- **Read vehicle instructions.** Review towing safety instructions in your towing/hauling vehicle manual.
- **Driver age.** You must be 16 years of age or older to operate the towing/hauling vehicle with the sprayer attached.
- **Check your local state regulations for further information regarding ATV use and laws.**
- **Securely attached.** Be sure sprayer is securely attached to the towing/hauling vehicle.
- **Tyres.** Make sure sprayer tyres are fully inflated and in good repair before towing. Do not over inflate. Serious injury could occur if tyre explodes.
- **Vehicle handling.** Be aware that vehicle handling will be affected when towing the filled sprayer. Exercise caution to avoid loss of control or sprayer overturning:
  - **Keep speed to a minimum** so you can maintain control at all times. Reduce speed prior to turning.
  - **Allow for wider turns and more distance to stop.**
  - **Avoid any sudden** steering maneuvers, starts, or stops that could create sway.
- **Rough or sloped terrain.** Slow down and exercise extra caution on rough or sloped terrain in order to reduce risk of rollover. Pick the most level route possible when transporting across fields. Drive up and down slopes that cannot be avoided, rather than across. Use a vehicle equipped with a Roll Over Protection System (ROPS) if you will be operating on non-level terrain.
- **BE AWARE of the added length of the sprayer and that visibility may be reduced** when making turns or backing up.
- **Ride / transport.** Never ride or transport cargo on the sprayer.
- **Under the influence.** Never tow or operate this sprayer while under the influence of alcohol, drugs, or medication
- **On public roads.** If towing on a public road, make sure to comply with all local, state, and federal towing requirements. It is the sole responsibility of the purchaser to obtain licensing, trailer lights, safety chains or signage as needed to comply.
- **Unattended.** Turn off both the sprayer and the vehicle, and set the brake or block the wheels, before leaving the sprayer unattended.

## Operation – Important Safety Information (cont'd)

### Chemical accident procedures:

#### **WARNING**

Before you fill the sprayer, review the following information with regard to handling accidents. Chemical spills, sprayer leaks, personal contamination, and poisoning are accident situations which you may encounter. **All require an immediate response – See instructions below.**

<b>Sprayer leak</b>	<p><b>In the event that the sprayer develops a leak while spraying chemicals, you must <i>immediately stop spraying</i>.</b></p> <p>Turn off power to the sprayer and follow the directions below, as applicable.</p>
<b>Bodily chemical contact</b>	<p><b>Personal contamination can occur when chemicals splash, spill, or spray directly onto a person.</b></p> <ol style="list-style-type: none"> <li>Follow the emergency first aid instructions on the chemical label listed in the "First Aid" or "Statements of Practical Treatment" section. <u>General procedures include:</u> <ol style="list-style-type: none"> <li>Eyes – immediately flush with water or follow other directions as specified on the chemical label.</li> <li>Skin – immediately wash all contaminated skin surfaces with soap and water, or follow directions as specified on the chemical label.</li> <li>Clothing – remove contaminated clothing immediately. Dispose of heavily contaminated clothing per the instructions on the chemical label for safe chemical/container disposal.</li> </ol> </li> <li>Seek medical advice if instructed on the label, or if the victim experiences symptoms of harmful effects such as burning, swelling, nausea, chest pain, difficulty breathing, dizziness or confusion. When seeking medical advice, be sure to bring the chemical product label.</li> </ol>
<b>Poisoning by ingestion or inhalation</b>	<p><b>In case of poisoning from ingestion or inhalation:</b></p> <p>IF THE VICTIM HAS COLLAPSED OR IS NOT BREATHING, <b><u>CALL 000</u></b>.</p> <p>Otherwise:</p> <ol style="list-style-type: none"> <li>If you are the victim, immediately seek assistance from nearby personnel because you may become incapacitated.</li> <li>Follow the emergency first aid instructions on the chemical label in the "First Aid" or "Statement of Practical Treatment" section.</li> <li>Call a poison control center for further advice. Have the chemical label available for reference. <b>In Australia. Call 13 11 26.</b></li> </ol>

## Operation – Important Safety Information (cont'd)

### Chemical spills

#### **Chemical spills must be quickly contained and properly cleaned up.**

Refer to the chemical label for any specific clean-up instructions with regard to the chemical spilled.

General procedures include:

1. **Control** the spill by stopping the source of the spill. If the source of the spill is a container leak, place the leaking container in a larger, watertight container. Keep unprotected people away from the spill site.
2. **Contain** the spill so that it does not spread and get into water sources. Use a shovel or other tool to make a dike around the spill with soil, sod, or absorbent material.
3. **Clean up** the spill immediately -- Absorbent materials like ground corncobs or pet litter should be spread on the spill area to soak up the pesticide. The contaminated material should then shoveled into a leak proof container. Do not flush the spill area with water until you receive advice as directed below.
4. **Seek additional advice** from the chemical manufacturer and your state's pesticide regulatory agency regarding decontamination of the spill site:
  - *Chemical manufacturer.* The chemical label provides contact information for the chemical manufacturer.
  - *State pesticide regulatory agency.*

## Operation – Preparing the Sprayer for Each Use


If the sprayer has been used previously, it must be prepared BEFORE EACH SUBSEQUENT USE.

### ⚠ WARNING

Read instructions below carefully for inspecting and preparing the sprayer.  
 Damaged or clogged equipment could result in leaks or uncontrolled spray.  
 Leaks could result in injury to the operator or bystanders from chemical exposure, or cause damage to the environment.

#### Important safety rules:

- **Power off.** Make sure all power is OFF before cleaning, inspecting, or servicing the sprayer.
- **Replacement parts.** If a part needs replacement, only use parts that meet the manufacturer's specifications. Replacement parts that do not meet specifications may result in a safety hazard or poor operation of the sprayer.

<b>1. Ensure sprayer attached</b>	<b>Ensure the sprayer is securely attached to the vehicle.</b>
<b>2. Ensure tank empty</b>	<b>Ensure the sprayer has been thoroughly flushed and drained of all residual chemical from prior uses.</b>
<b>3. Clean suction strainer</b>	<p><b>Clean the suction strainer of any chemical residue.</b>                      It is important to clean the suction strainer before each use to ensure it is not clogged and to prevent residual chemical from contaminating sprayer contents.  <b>IMPORTANT:</b> The strainer must be accessed by reaching into the tank, so the <i>tank must be empty</i> to avoid immersing your hand in chemicals.</p> <ol style="list-style-type: none"> <li>a) Open fill cap on top of tank.</li> <li>b) USING RUBBER GLOVES, reach into the tank and pull the suction strainer off the end of the suction tube. (See figure below.)</li> <li>c) Run the suction strainer under fresh water to remove debris.</li> <li>d) Replace the suction strainer onto the end of the suction tube.</li> </ol> <div style="text-align: center; margin-top: 20px;">  <p style="text-align: right; margin-right: 50px;">Suction strainer located inside tank</p> </div>
<b>4. Inspect &amp; repair</b>	<p><b>Inspect and test the sprayer thoroughly:</b></p> <ol style="list-style-type: none"> <li>a) Inspect hoses for exposed mesh and holes. Replace all worn or damaged hoses.</li> <li>b) Inspect tank and fittings for cracks and leaks. Replace all damaged fittings with original Kinchrome parts.</li> <li>c) Check to be sure retaining nut on gun nozzle is tight.</li> <li>d) Check to be sure all other nuts, bolts, and screws are tight.</li> <li>e) Prior to use, make sure wheel are assembled correctly and tyres are inflated.</li> <li>f) <i>Partially fill tank with plain water and spray to test for leaks.</i> Repair as needed.</li> </ol> <p><b>IMPORTANT:</b> <i>After any repair work has been done, ALWAYS test for leaks with water one final time before using.</i></p>

## Operation – Using the Sprayer

### **Step One: Assess wind conditions and clear work area.**

Before you decide to spray, you must determine whether wind conditions are suitable. You must also restrict access to the work area to ensure the safety of bystanders.

#### **WARNING**

Do not spray if wind speeds are greater than 6.5 km/h or if there are bystanders in the intended spray area.

<b>1. Assess wind speed</b>	<b>Assess weather conditions to ensure that it is not too windy to spray.</b> <b>DO NOT SPRAY if wind speeds are greater than 6.5 km/h.</b>  <i>Visible indication of wind speed:</i> If leaves are in constant motion or there is any branch movement, DO NOT spray because the wind is too strong.
<b>2. Clear work area</b>	<b>Clear the work area of all bystanders and pets.</b> Restrict access by the public for the period recommended on chemical label.

## Operation - Using the Sprayer (cont'd)


### **Step Two: Fill the sprayer.**

#### **⚠ WARNING**

ALWAYS wear personal protective equipment as directed on the chemical label when handling pesticides.

Long pants and sleeves, chemical resistant gloves, and eye protection are strongly recommended. Additional protective gear may be required depending on the particular pesticide.


### **Fill the sprayer using the following steps:**

<b>1. Review safety information</b>	<b>Review the "Operation – Important Safety Information" related to <u>General Chemical Safety</u> and <u>Chemical Accident Procedures</u> provided in this manual.</b>
<b>2. Choose safe mixing/loading area</b>	<b>Choose a safe pesticide mixing and loading area.</b> - Choose an outdoor, well-ventilated area away from unprotected people, animals, food, and other items that might become contaminated.
<b>3. Wear personal protective equipment</b>	<b>Wear personal protective equipment as directed on the chemical label.</b> - Note that additional equipment may be specified for mixing and loading activities.
<b>4. Turn off sprayer and vehicle</b>	<b>Turn OFF power to the sprayer before filling.</b> - The vehicle should also be off, with brake set or wheels blocked to prevent unintended movement.
<b>5. Remove fill cap</b>	<b>Remove the fill cap located on top of the sprayer.</b> <div style="text-align: center; margin-top: 20px;">  <p style="font-size: small; margin-top: 5px;">Fig05656c</p> </div>
<b>6. Ensure tank flushed</b>	<b>Ensure tank is flushed of all chemicals from prior uses.</b> - Chemicals can interact dangerously when mixed, and residue chemicals are also a health hazard.

## Operation - Using the Sprayer (cont'd)

### 7. Check drain cap


Before filling tank, ensure drain cap is securely tightened.



### 8. Fill tank

**Add pesticide to tank through fill cap:**

- Confirm the chemical/water dilution ratios specified on the chemical label.
- Determine chemical and water volumes needed for the planned application, taking into consideration that maximum tank capacity is 50 litres/13 gallons.  
*Note: Only purchase and mix as much chemical as you need for the planned application in order to minimize chemical over application and the need for storing unused chemicals.*
- Add chemical to the tank through the fill cap.  
*If the chemical is not pre-mixed, add water and pesticide concentrate in the order prescribed on the label.*



### 9. Ensure chemical mixed

**Ensure chemical is thoroughly mixed in tank.**

- Stirring device should be made of metal or plastic, non-chemical absorbing material, and then properly cleaned and stored after use.

### 10. Replace fill cap

**Replace fill cap and tighten securely.**

## Operation - Using the Sprayer (continued)



### **Step 3: Operate the sprayer.**

#### **⚠ WARNING**

ALWAYS wear personal protective equipment as directed on the chemical label when spraying.

Long pants and sleeves, chemical-resistant gloves, and eye protection are strongly recommended. Additional protective gear may be required depending on the particular pesticide.

The motor surface temperature can reach temperatures over 70° C. In order to avoid scalding, wear gloves during operation of the sprayer.


<b>1. Review safety information</b>	<b>Review the "Operation – Important Safety Information" related to <u>Chemical Application Safety</u> and <u>ATV Vehicle Handling Safety</u> provided in this manual.</b>
<b>2. Wear personal protective equipment</b>	<b>Wear personal protective equipment as directed on the chemical label.</b>
<b>3. Set Cut Off Limit</b>	<ul style="list-style-type: none"> <li>• With the regulator open, apply proper electrical power and purge pump of air.</li> <li>• Slowly close pressure regulator until the pump begins to cycle (on/off within 2 sec). Adjust the set screw clockwise (raise) or counterclockwise (lower) until the "cut-off" pressure is within 2 psi (using the attached pressure gauge) of the psi indicated on the motor label.</li> <li>• Open the pressure regulator and repeat previous step several times to verify pressure switch adjustment.</li> <li>• If the pressure regulator knob is completely tightened, the pressure setting will be higher than the pressure switch on the pump (40 psi). This allows the pump to operate as a demand pump and turn on only when spraying. When the pressure is set below the pump maximum (40 psi), the pump will continuously run, bypassing fluid back into the tank for agitation.</li> </ul> <div style="text-align: center; margin-top: 20px;">  <p style="margin-left: 100px;">FIG05618</p> </div> <div style="margin-top: 10px;"> <p>Cut Off Limit Set Screw</p>  </div>



## Operation - Using the Sprayer (continued)

**4. Close broadcast boom valve**

Close broadcast valve to prevent accidental spray release.



**5. Turn on power**

**Turn on the power to the sprayer.**

1. Verify the remote switch is connected to the pump power cord.
2. Turn the remote switch to the "ON" position.

*Note: The pump will start automatically when power is turned on. The pump will cycle on and off as needed to retain pressure in the hose.*

**6. Adjust pressure regulator**

**Turn pressure regulator knob to adjust outlet pressure**

- 1. Turn knob clockwise to increase pressure.**
- 2. Turn knob counter-clockwise to decrease pressure**

Note: If the pressure regulator knob is completely tightened, the pressure setting will be higher than the pressure switch on the pump (40 psi). This allows the pump to operate as a demand pump and turn on only when spraying.

**7. Begin agitation if needed**

**Some formulations of liquid pesticides do not remain in solution and should be agitated to maintain a uniform mix.**

The pressure regulator on this sprayer can be used as an agitator. If the pressure is set below the pump's pressure switch setting (70 psi), the pump will continue to run even when not spraying. Fluid will be diverted through the pressure regulator back to the tank. This bypass fluid will keep the contents of the tank well-mixed, and allow the sprayer to be used with pesticides classified as "flowable" ("F" or "L"), "wettable powder" ("WP" or "W"), "emulsion" ("EC" or "I"), microencapsulated ("M"), or "water dispersible granules" ("WDG" or "DF")


## Operation - Using the Sprayer (continued)

### 8. Squeeze trigger & adjust nozzle

To spray, squeeze the gun trigger.


- Twist the spray nozzle to adjust from a straight stream to hollow cone spray pattern, as recommended on the chemical label for proper delivery rate.

*Note: It is not unusual for the operator to be exposed to chemical drips while adjusting the nozzle – gloves should be chemical resistant.*



### 9. Operate broadcast boom


#### A. Open rear broadcast spray nozzle valve



## Operation - Using the Sprayer (continued)

### B. Ensure correct spray pattern

Make sure the boom nozzle is pointed straight down. If it is not, loosen the nozzle retaining nut, orient the opening of the boom nozzle to point straight down, then retighten the nozzle retaining nut.



**IMPORTANT:** Make sure broadcast nozzle is oriented to spray downwards, parallel with the ground, before you start. An incorrectly positioned broadcast nozzle may spray chemicals on you or others.

**Note:** It is not unusual for the operator to be exposed to chemical drips while adjusting the broadcast nozzle. Chemical resistant gloves should be worn.


## Operation - Using the Sprayer (continued)

### C. Ensure uniform coverage

To ensure proper coverage, the height of the broadcast nozzle should be about 500mm from the ground. The sprayer must be level with the ground to get this height.

The overall spray width is 2 meters, but 1/2 or 1 meter of the overall spray pattern must be overlapped to get equal coverage throughout the spray area.

Use the tables in Appendix A to determine what speed to drive your vehicle for the desired application rate.



### D. Begin to spray

Turn the remote switch ON to begin spraying.

#### 10. Leaving unattended

**If the sprayer must be left unattended at any time:**

- a) Disconnect power to the sprayer.
- b) Relieve system pressure by depressing the gun trigger.
- c) Turn off the vehicle. Set brake or block the wheels.

#### 11. Discontinue use if clogged or inoperative

**If the sprayer becomes clogged or inoperative during use, *discontinue use immediately.***

- DO NOT attempt to service while chemicals are in the sprayer and power is connected.
- Return to service area to review instructions for troubleshooting before attempting to service.

**Note:** A reserve, clean container capable of holding at least 50 litres should be kept for use when the sprayer tank needs to be emptied temporarily for repairs. The container should be properly labeled as to its contents if it is used.

## Operation - Using the Sprayer (continued)

### **Step 4: Clean sprayer and decontaminate after use.**

When done using the sprayer, it is important to clean the sprayer and decontaminate yourself. Do not store the sprayer with chemicals in the tank, as it is unsafe and could also result in damage to the equipment.

#### **WARNING**

Clean-up and decontamination procedures must be followed after each use.

Improper equipment clean-up and disposal of chemicals can result in dangerous chemical exposure to humans and the environment, as well as equipment damage.

Personal decontamination is required after spraying to minimize unsafe exposure to chemicals and potential illness.

<b>1. Drain tank</b>	<b>If there is excess pesticide left in the tank, drain the tank:</b> <ol style="list-style-type: none"> <li>a) Disconnect power to the sprayer and relieve system pressure by depressing the gun trigger.</li> <li>b) Find a suitable container in which to drain the unused pesticide. Place it under the tank drain hole.</li> <li>c) While wearing rubber gloves, eye protection, and all other required personal protective equipment, remove the drain cap and allow pesticide to drain into container.</li> <li>d) When tank stops draining, replace drain cap. Tighten securely.</li> </ol>
<b>2. Unused chemical</b>	<b>Properly store or dispose of unused chemical:</b> <ol style="list-style-type: none"> <li>a) <u>If the unused pesticide is to be stored for future use:</u> Store all unused pesticide in its original, or a suitably marked, container in a secure location out of the reach of children &amp; animals.</li> <li>b) <u>If remaining pesticide is to be disposed:</u> Properly dispose of the remaining chemical and its container per the chemical manufacturer's recommendation and according to local hazardous waste disposal regulations.</li> </ol>
<b>3. Flush sprayer</b>	<b>Flush the sprayer per the chemical manufacturer's recommendations.</b> A general procedure is as follows: <ol style="list-style-type: none"> <li>a) Add fresh water to the tank.</li> <li>b) Reconnect power to the sprayer.</li> <li>c) Operate the spray gun and discharge all rinse water onto an area that can accept dilute pesticide application.</li> <li>d) Add 19 litres of the chemical manufacturer's recommended cleaning solution. Operate the spray gun, collecting the discharged solution if recommended by the manufacturer.</li> <li>e) After flushing, disconnect power to the sprayer and be sure all system pressure is relieved by squeezing the gun trigger.</li> <li>f) Dispose of cleaning solution discharge as recommended by the manufacturer of the solution.</li> </ol>
<b>4. Decontaminate &amp; launder</b>	<b>Decontaminate yourself after you are finished handling chemicals:</b> <ol style="list-style-type: none"> <li>a) Remove all clothing worn during spraying and chemical handling.</li> <li>b) Wash all exposed parts of the body with soap and water.</li> <li>c) Launder clothing separately from other wash.</li> </ol>

## Storage

Prepare the sprayer for end-of-season storage by running antifreeze through the system. This will keep internal parts lubricated, protect against corrosion, and keep the unit from freezing.

### CAUTION

The sprayer will be damaged if it freezes.  
Protect the sprayer from freezing during storage by following the instructions below.

#### Preparing for storage:

<b>1. Add antifreeze</b>	Pour 4 litres of Propylene Glycol based antifreeze into the tank.  <b>Some antifreeze contain Ethanol (which is alcohol based and highly flammable.) which should not be used.</b>
<b>2. Spray briefly</b>	Turn on the pump motor and squeeze the gun trigger briefly until fluid sprays. Store gun in the lance clips located on the side of the tank.

#### Removing from storage:

<b>1. Drain</b>	Drain the antifreeze left in the tank through the tank drain hole into a suitable container.
<b>2. Flush with water</b>	Fill the tank with fresh water and run through the system. Operate the spray gun until the system is completely flushed. Be sure to set up containers to capture the antifreeze flush water.
<b>3. Disposal</b>	Dispose of the antifreeze and flush water properly.

## Troubleshooting

### WARNING

Before troubleshooting or attempting to service, read the following safety rules to avoid accidental exposure to chemical and also risk of electric shock.

***Note:** A reserve, clean container capable of holding at least 50 litres should be kept for use when the sprayer tank needs to be emptied temporarily for repairs. The container should be properly labeled as to its contents if it is used.*

#### **Before attempting to service the sprayer:**

<b>1. Personal protective equipment</b>	<b>Wear personal protective equipment as directed on the chemical label while servicing your sprayer.</b>
<b>2. Review troubleshooting table</b>	<b>Review the Troubleshooting Table below for the type of problem you are experiencing.</b> However, DO NOT attempt to repair until the steps listed below are followed.
<b>3. Empty and flush</b>	<p><b>If the cause listed for your problem is Clogged intake tube, Clogged suction strainer, or Worn spray gun nozzle:</b> empty the tank and flush the sprayer with water as directed in the section, "Operation – Step Four".</p> <p><i>- In order to avoid accidental exposure to chemicals, never attempt to unclog the intake tube or suction strainer, or service the spray gun nozzle, until the tank has been emptied and the sprayer flushed with water.</i></p>
<b>4. Disconnect power/relieve pressure</b>	<b>Disconnect power to the sprayer and be sure all system pressure is relieved by squeezing the gun trigger.</b>
<b>5. Perform repairs</b>	<p><b>Follow the directions provided in the troubleshooting table to repair the sprayer.</b></p> <p><i>NOTE: Never try to unclog the sprayer nozzle by blowing through it.</i></p>
<b>6. Test after servicing</b>	<b>After servicing, ALWAYS test the sprayer for leaks with plain water before using.</b>

## TROUBLE SHOOTING

PROBLEM	CAUSE	SOLUTION
Pump will not turn on	Bad electrical connection	Check battery connections
	Fuse blown	Replace fuse
	Short in wires	Check condition of wires
	Low voltage	Check voltage
Low pressure	Worn spray gun nozzle	Replace spray gun
	Worn broadcast nozzle	Replace broadcast nozzle
	Pressure set too low	Adjust pressure regulator
	Leaking fitting/Hose	Check for leaks and tighten leaking fittings.
Low flow	Clogged intake tube	Remove obstruction
	Clogged suction strainer	Clean suction strainer
	Incorrectly set regulator	Adjust regulator pressure.
	Pressure set too low	Adjust pressure regulator
Poor spray distribution	Low voltage	Check voltage
	Clogged intake tube	Remove obstruction
	Suction strainer clogged	Clean suction strainer
	Worn spray gun nozzle	Replace spray gun
Pump cycles while not spraying	Too low a pressure.	Set correct pressure.
	Leak in the system Pressure set to low and bypassing.	Tighten leaking hose clamps or fittings, replace spray gun. Set correct pressure.



## SPECIFICATIONS

### Electrical System Requirements

Electrical connection	12 VDC
Amp draw from pump	3.0 Amps

### Sprayer Specifications

Maximum GPM	3.8 Litres/min
Maximum Pressure	40 PSI (2.76 Bar)

Tank Maximum Capacity	50 Litres
-----------------------	-----------

### Overall Dimensions

Length:	93cm (drain plug to edge of hitch)
Width:	56cm (wheel to wheel)
Height:	600cm (ground to top of pressure regulator)
Ground Clearance:	11cm (Ground to bottom of Axle)

Dry Weight / Weight full of water	12.3kg /62.3kg
Spot Sprayer Delivery Hose Length:	4.5m

### Broadcast Nozzle Specifications

Effective Spray Width	203.2 cm
-----------------------	----------

### Component Materials\*

Tank.....	Polyethylene, EPDM
Suction Tube.....	Polypropylene, PVC, Stainless Steel
Hose.....	PVC, EPDM (Max. Pressure 6.9Bar/100 psi)
Pump.....	Polypropylene, Viton®, Santoprene, Stainless Steel
Valves.....	Polypropylene, Polyacetal, Viton®, Nylon
Spot Spray Gun and Nozzle	Nylon, Polyacetal, Aluminum

\*Before using any chemical, check to ensure the chemical is compatible with all materials in the system.

The noise emissions from this product do not exceed 70 dB(A).


Note: The sprayer is not compatible with bleach or chlorine products. Also, pumping any petroleum based fluid (gasoline, diesel, kerosene, oil) will severely damage the pump.

The manufacturer reserves the right to make improvements in design and/or changes in specifications at any time without incurring any obligation to install them on units previously sold.

**Any Questions, Comments, Problems or Part Enquiries**

***Call Kincrome Customer Service on 1300 657 528***

# Exploded View – K16003 50 Litres Tow Behind Sprayer



## Exploded View – K16003 50 Litre Tow Behind Sprayer

Ref#	Part#	Supplier#	Description	Qty
1	K16003-1	5230	Broadcast Nozzle Nut	1
2	K16003-2	5232	Drain Plug/Cap Rubber Washer	1
3	K16003-3	5383	Broadcast Nozzle Housing	1
4	K16000-2	30746	10mm (3/8)" Hose clamp	8
5	K16003-5	37680	Drain Cap/Plug	1
6	K16003-6	791504	(Spray Gun Storage Clip Screw) #10-24 x 10mm Screw	7
7	K16003-7	82286	Wheel Washer	4
8	K16001-13	777110	Hose Guide (P-Clip)	1
9	K16003-9	792605	Broadcast Nozzle	1
10	K16003-10	777853	Nozzle Retaining Nut	1
11	K16003-11	82065	#10-24 Nyloc Nut	1
12	K16000-12	778560	Spray Gun Mounting Clip	3
13	K16000-9	780544	Suction Strainer/Filter	1
14	K16003-14	789074	Wheel/Tyre	2
15	K16003-15	797474	3.8 LPM Kincrome Pump	1
16	K16003-16	790802	Spot Sprayer Gun Assembly	1
17	K16003-17	797523	Rear Tank Mounting Bracket	2
18	K16003-18	797481	Lower Hose Storage Hook	1
19	K16003-19	797479	Upper Hose Storage Hook	1
20	K16003-20	797487	Tow Bar	1
21	K16003-21	792304	Axle	1
22	K16003-22	797488	Front Bracket	1
23	K16003-23	797486	Hitch	2
24	K16003-24	794111	Tank Cap	1
25	K16003-25	793136	50 Litre Tank	1
26	K16003-26	797485	Broadcast Bracket	1
27	K16003-27	792416	Axle Pin	2
28	K16003-28	792888	Pump Mounting Bracket	1
29	K16003-29	792424	Broadcast Valve	1
30	K16003-30	792425	Suction Hose	1
31	K16003-31	792453	Grommet	1
32	K16003-32	792535	Draw Tube Hose	2
33	K16003-33	794454	3/8" Spray Gun Hose	1
34	K16003-34	792562	3/8" Outlet Hose	1
35	K16003-35	791998	Draw Tube Grommet	1
36	K16003-36	797476	Kincrome Tank Decal	1
37	K16003-37	797475	Kincrome Pump Label	1
38	K16000-5	777493	Wire Harness w/ Remote Switch	1
39	K16003-39	35363	Hook and Loop Set	1
40	K16003-40	784519	Regulator Grommet	1
41	K16003-41	82616	#10-24 x 15mm Screw	3
42	K16001-15	779854	1/4" Male NPT x 3/8" Hose Barb	1
43	K16003-43	795848	Pressure Regulator	1
44	K16003-44	787196	QC x 3/8" Hose Barb Elbow	1
45	K16003-45	791465	Pressure Gauge	1
46	K16003-46	787193	QC x 1/2" Hose Barb	1
47	K16003-47	797482	Kincrome Branding Decal	1
48	K16001-3	82061	#10-24 x 25mm Screw	1
NA	K16004-60	797473	Kincrome Warning Label	1

## Appendix A –Broadcast Spray Calibration Tables

Below are some guidelines to help you calibrate your tow behind broadcast sprayer. This is a very important step in operating the tow behind broadcast sprayer such that too much or too little chemical may be applied.

1. Using **Table 1**, find a table that corresponds with the chemical manufacturers suggested application rate (litres per hectare, litres per 100 sq. m., or litres per 10 sq. m.).
2. Find the application rate that is closest to the chemical manufacturer's recommendations.
1. The speed to drive your ATV is listed below the application rates.

**TABLE 1**

Spray Height	Pressure (kPa)	Litres per Hectare – based on water at 101cm spacing						
		1 KM/H	3 KM/H	5 KM/H	7 KM/H	9 KM/H	12 KM/H	16 KM/H
53 cm	69	147.1	49.0	29.3	21.0	16.3	12.2	9.2
53 cm	138	209.6	69.9	41.8	29.9	23.2	17.4	13.1
53 cm	207	253.7	84.6	50.6	36.2	28.1	21.1	15.8
53 cm	276	294.1	98.0	58.6	41.9	32.6	24.4	18.3

Spray Height	Pressure (kPa)	Litres per 100 Sq.m. - based on water at 101cm spacing						
		1 KM/H	3 KM/H	5 KM/H	7 KM/H	9 KM/H	12 KM/H	16 KM/H
53 cm	69	1.47	0.49	0.29	0.21	0.16	0.12	0.09
53 cm	138	2.10	0.70	0.42	0.30	0.23	0.17	0.13
53 cm	207	2.54	0.85	0.51	0.36	0.28	0.21	0.16
53 cm	276	2.94	0.98	0.59	0.42	0.33	0.24	0.18

Spray Height	Pressure (kPa)	Litres per 10 Sq.m. – based on water at 101cm spacing						
		1 KM/H	3 KM/H	5 KM/H	7 KM/H	9 KM/H	12 KM/H	16 KM/H
53 cm	69	0.15	0.05	0.03	0.02	0.02	0.01	0.01
53 cm	138	0.21	0.07	0.04	0.03	0.02	0.02	0.01
53 cm	207	0.25	0.08	0.05	0.04	0.03	0.02	0.02
53 cm	276	0.29	0.10	0.06	0.04	0.03	0.02	0.02

\* Approximate flow from one nozzle

2. Use **Table 2** to choose the throttle setting on your ATV.

**TABLE 2**

Speed (KM/H)	Time required in seconds to travel a distance of:		
	10 m.	50 m.	100 m.
1	36	180	360
3	12	60	120
5	7	35	70
7	5	25	50
9	4	20	40
12	3	15	30
16	2	11	22

5. The coverage area can be found by dividing tank size by the application rate.

**Example:** 50 litres divided by 100 litres/hectare = 0.50 hectare of coverage per tank.

## Limited Warranty

Dear Valued Customer:

Use this product properly and enjoy the benefits from its high performance. By purchasing a Kincrome product, you show a desire for quality and durability. Like all mechanical equipment this unit requires a due amount of care. Treat this unit like the high quality piece of machinery it is. Neglect and improper handling may impair its performance. Please thoroughly read the instructions and understand the operation before using your product. Always contact Kincrome Customer Service on 1300 657 528 prior to having any service or warranty work performed, as some services performed by parties other than Kincrome approved service centers may void this warranty. This warranty is in lieu of any other warranty expressed or implied and Kincrome assumes no other responsibility or liability outside that expressed within this warranty.

### **Australian Limited Warranty**

Warranty given by Kincrome Australia Pty Ltd of 3 Lakeview Drive, Caribbean Park, Scoresby, Victoria (Tel 1300 657 528). The applicable warranty period (24 months) commences on the date that the product is purchased. If this product has materials or workmanship defects (other than defects caused by abnormal or non warranted use) you can, at your cost, send the product to place of purchase, an authorised Kincrome service agent or one of Kincromes addresses for repair or replacement. Your rights under this warranty are in addition to any other rights you have under the Australian Consumer Law or other applicable laws. Our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and compensation for any other reasonably foreseeable loss or damage. You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality and the failure does not amount to a major failure. For further details please visit [www.kincrome.com.au](http://www.kincrome.com.au) or call us. Due to minor changes in design or manufacture, the product you purchase may sometimes differ from the one shown on the packaging. **IMPORTANT!** If the tool fails to operate correctly, call customer service on 1800 657 528 for advice on the best resolution for your situation. If a resolution cannot be achieved over the phone please take the tool and all related accessories to an authorised service centre or place of purchase showing proof of purchase for assistance.



Kincrome Tools and Equipment  
3 Lakeview Drive, Scoresby VIC 3179  
Melbourne, Victoria  
[www.kincrome.com.au](http://www.kincrome.com.au)